



<b>Design</b>	Egoé studio	
<b>Character</b>	Stand for double-sided bicycle parking. For soft contact with the bicycle or scooter, a rubber belt is attached to the supporting steel structure. Recommended spacing between stands is 650 to 750 mm [25.5" - 29.5"].	<b>Charakter</b>
<b>Materials</b>	The support frame of the rack consists of a welded single leg made of closed steel section and steel banding. The overhanging rubber strip is fixed to the structure with a steel rail and stainless steel fasteners. The surface treatment of the steel elements consists of a corrosion-protective zinc coating and a powder coating. The colour in a fine matt texture can be selected according to „ <a href="#">Samplers RAL</a> “.	<b>Werkstoffe</b>
<b>Anchoring</b>	Anchoring to the concrete subfloor under the pavement using M8 threaded rods according to the valid anchorage drawing. All elements of the street furniture must be properly anchored, otherwise there is a risk of the product falling over during careless use, for which the manufacturer is not responsible.	<b>Verankerung</b>
<b>Maintenance</b>	Use the usual cleaning methods suitable for street furniture, see the manual „ <a href="#">Inspection and maintenance</a> “.	<b>Wartung</b>
<b>Weight</b>	7.5 kg [16.5 lbs]	<b>Gewicht</b>

**Technical Sheet / technisches Arbeitsblatt**

The dimensions of the products are informative. We reserve the right to change the specifications without notice. For the most current version of this document please refer to our website. Die Abmessungen sind informativ. Wir behalten uns das Recht vor, die Spezifikationen ohne vorherige Ankündigung zu ändern. Die gültige Version dieses Dokuments finden Sie auf unserer Website.